

Technical Specifications

TL-ADPT-02

Features at a Glance

- Converts USB 3.1 type-C to HDMI
- Male USB 3.1 type-C connector to female HDMI connector
- Dongle design reduces stress on devices
- 6 inch long dongle
- 4K@30 compliant
- No power required
- Supports three display modes (mirror, extended and primary)
- Plug-and-play, no driver required



The TL-ADPT-02 adapts a USB type-C enabled source to an HDMI enabled display.

Specifications

I/O Connections	
Input	1 x USB Type-C
Output	1 x HDMI
Input/Output Signal Type	USB 3.1 Type-C and HDMI 1.4
Input/Output Resolution Support	800x600@60Hz, 1024x768@60Hz, 1280x720P@60Hz, 1280x768@60Hz, 1280x800@60Hz, 1280x960@60Hz, 1280x1024@60Hz, 1366x768@60Hz, 1366x768@60Hz, 1400x1050@60Hz, 1440x900@60Hz, 1600x900@60Hz, 1600x1200@60Hz, 1680x1050@60Hz, 1920x1080P@60Hz, 1920x1200@60Hz, 2048x1536@60Hz, 2560x1440@60Hz, 2560x1600@60Hz, 3840x2160@30Hz;
General	
Operating Temperature	32°F to 113°F (0°C to 45°C) 10% to 90%, non-condensing
Storage Temperature	-4°F to 140°F (-20°C to 70°C) 10% to 90%, non-condensing
Humidity	10% to 90%, non-condensing
Cable Length	105mm
Product Dimension (W x H x D)	55mm x 16mm x 45mm
Product Weight	20g
ESD Protection	Human-body Model: ±8kV (Air-gap discharge)/±4kV (Contact discharge)
Warranty	3 years