The Intelix AVO-V1-WP-F wall-plate balun transmits one composite video signal over standard structured cabling, such as Cat 5. Used in pairs or with a rackmountable Intelix AVO-V1-F balun, AVO-V1-WP-F baluns replace bulky coaxial video cable and transmit a video signal up to 2,200 feet.

The Intelix AvoCat Series of baluns is the ideal solution for sending video over structured cabling. When signal quality matters, choose Intelix.


> Attenuation: 6.6 dB/1000 ft. @ 1 MHz Cat 5, Cat 5e, Cat 6, Cat 7 compatible



## Technical Specifications

Maximum Distance*	2,200 feet	Connectors	One (1) female RCA to one (1) RJ45
Maximum Input	1.1 Vp-p	RJ45 Pinout	7 & 8, pair 4
Bandwidth	DC to 8 MHz	Temperature	Operating: 32 to 131 F (0 to 55 C)
Impedance	75 ohms		Storage: -4 to 185 F (-20 to 85 C) Humidity: up to 95%
Insertion Loss	Less than 2 dB over the frequency range	Enclosure	Front: standard decora wall plate Rear: metal casing
Return Loss	Greater than 15 dB over the frequency range	Dimensions	4.0" x 1.4" x 1.7"
Common Mode Rejection	Greater than 40 dB over the frequency range	Ordering Information	AVO-V1-WP-F: single AVO-V1-WP-F in bulk packaging
Unshielded Twisted Pair Cabling Specifications	Maximum capacitance: 20 pf/foot Impedance: 100 ohms @ 1 MHz	Warranty	Two years

<sup>\*</sup>Distances and picture quality may be affected by cable grade, cable quality, source and destination equipment, RF and electrical interference, and cable patches. Intelix specifications are based on straight-through cabling with standard-grade Cat 5.





(24 gauge or lower solid

copper)

player is distributed over Cat 5 cabling to a remote video switcher. The DVD player connects to an Intelix AVO-V1-WP-F wall plate balun and an Intelix AVO-V1-F composite video balun connects directly to the composite video switcher.







Phone: 608-831-0880 Toll-Free: 1-866-4-MATMIX Fax: 608-831-1833