



Tired of problem installations? Rethink HDMI with the Intelix DIGI-HD-UHR2.

The Intelix DIGI-HD-UHR2 transmits HDMI up to 300' over a single twisted pair cable. Built-in HDshāk® technology provides dynamic HDMI, EDID/DDC and HDCP mode selection, guaranteeing performance and image quality. Plus, onboard HDMI amplification and buffering allows multiple extenders to be daisy-chained for greater distances.

The DIGI-HD-UHR2 features electrostatic discharge (ESD) protection circuitry which safeguards the HDMI circuit against static electricity and other destructive stray voltage.

Design with Intelix and Design with Intelligence.

Maximum Distance (Cat 5e)	1080p: 100' 1080i/720p: 200'	Maximum Daisy-Chains	3 sets (approx. 450' w/Cat 5e)
Maximum Distance (Cat 6)	1080p: 150' 1080i/720p: 300'	Operating Temperature Range	-41 to 95 degrees F -5 to 35 degrees C
Supported Video Resolutions	480i, 480p, 576i, 576p, 720p, 1080i, 1080p 8, 10, 12 bits per channel	Operating Humidity Range	5 to 90% non-condensing
Supported Audio	Dolby TrueHD 7.1, Dolby TrueHD 5.1, Dolby Digital 5.1, DTS-HD Master Audio 7.1, DTS-HD Master Audio 5.1, DTS 5.1, PCM 2.0, PCM 5.1	Dimensions	4.38" x 2.50" x 1.00"
Video Amplifier Bandwidth	1.65 Gbps	Enclosure	metal
Output Video	HDMI 1.3 with HDCP	Max Power Consumption	1.5 watts
Compliance	HDMI 1.3b, HDCP	Power Supply Requirement	power required on send and receive end
Input DDC Signal	5.0 volts p-p (TTL)	Power Regulatory	5 VDC CE, RoHS
Input Video Signal	0.5 to 1.0 volts p-p	Shipping Weight	1 lbs.
Cabling	one twisted pair cable required; minimum grade of Cat 5e	Intelix Part Number	DIGI-HD-UHR2
Connectors	one (1) HDMI one (1) shielded RJ45	ESD Protection	yes
		Diagnostic Indicators	power and status LEDs
		Included Accessories	(2) power supplies
		Mounting	AVO-CLIP-F
		Similar Part Numbers	DIGI-HD-UHR2-S: transmitter DIGI-HD-UHR2-R: receiver
		Warranty	2 years

